






HSF RoHS

SPECIFICATIONS PERFORMANCE

Electical Rating: AC/DC 50V 0.5A
 Insulation Resistance: 500MΩ
 Contact Resistance: 50mΩ Max
 Withstang Volt: 150V AC/minute
 Opratng Temperature: -40°C to +125°C
 Material
 Contact: Phosphor Bronze Gold-Plated
 Insulator Material: Polyester (UL94V-0)
 Housing: LCP
 Max. Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)



PCB LAYOUT

Ordering Information

3710 F XXX 038 G3 F X 01

No. of Pins 24P ~140P	Plastics Height H=3.8	Contact Plating G0: Gold Flash G2: 1.5U" Gold G3: 2U" Gold G4: 3U" Gold G5: 30U" Gold S0: Gold Flash/Tin	Insulator Material Option D=BK-PA46 F=BK-LCP E=PA9T	Post A=Tray T=Tube R=Tape&Reel P=Tube+Cap
-----------------------------	--------------------------	--	---	---

P数	A	B	C	D	E	F	G
24	8.80	11.24	13.70	15.36	10.84	12.38	13.80
40	15.20	17.64	20.10	21.76	17.24	18.78	20.20
60	23.20	25.64	28.10	29.76	25.24	26.78	28.20
80	31.20	33.64	36.10	37.76	33.24	34.78	36.20
100	39.20	41.64	44.10	45.76	41.24	42.78	44.20
120	47.20	49.64	52.01	53.76	49.24	50.78	52.20
140	55.20	57.64	60.01	61.76	57.24	58.78	60.20

OPERATION		DRAW	Ben	17.06.10	SCALE	FIT
X.X	±0.30					
X.XX	±0.20	CHECK			UNIT	mm
X.XXX	±0.10					
Angle	±3°	APPROVE			SHEET	1/1
DIM	TOL					
PROJ.						

JILN 深圳市锦凌电子有限公司
 SHENZHEN JINLING ELECTRONIC CO.,LTD
 Tel: 86-755-2997-5806/5802 Fax: 86-755-2997-5992

PART NO.	3710FXX038G3FX01
TITLE:	0.8BTB-NPIN H=3.8 Female

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
B	2017.06.10	change post size 1.15 — 1.05	
A	2014.03.29	NEW DRAWING	